

REMARKS

In this broadening reissue application, claims 1-23, 28-34, and 40-67 were pending at the time of the CFI decision. Claims 24, 25, 35, 36, 37, 38, 39, 41-49, and 50-58 have previously been cancelled without prejudice. The Examiner allowed claims 1-23, 28-34, 40-58, and 62-67 upon filing a supplemental reissue declaration. Claims 59-61 stand rejected as being anticipated by Cordell. Claims 59 and 61 have been amended and new claims 68 and 69 have been added by this response to place the application in condition for allowance. As discussed below, all of the pending claims are in condition for allowance.

BEST AVAILABLE COPY

Original Patent

The Assignee will surrender the original patent, or will submit a declaration as to loss or inaccessibility of the original patent, after the Examiner allows all of the pending claims.

Oath

The Applicant will file a supplemental reissue declaration upon completion of prosecution and satisfaction of the Examiner's objections and/or rejections to the claims.


Rejection of Claims 59-62 under 35 U.S.C. § 102(b) **in View of U.S. Patent 4,350,904 to Cordell**

Claim 59 as amended recites a method comprising sinking from a node a reference current having a first temperature coefficient; sourcing to the node a current having approximately the first temperature coefficient and being related to a power-supply voltage; and comparing the reference current to the supply-related current. Claim 61 was amended to modify an antecedent basis reference. The attached "Marked Up of the Claims 59 and 61, and New Claims 68 and 69" shows the textual changes to claims 59 and 61.

For example, referring to the illustration sketched below, a reference current I_{ref} having a first temperature coefficient is sunk from a node N and a current I_{sup} having approximately the first temperature coefficient and related to a power-supply voltage

(If integrated as V_{cc}) is sourced to the node N. The voltage at the node N indicates the magnitude of I_{ref} relative to I_{sup} . By comparing this voltage to a known voltage, one effectively compares I_{ref} to I_{sup} .

The following sketch is a simplification of FIG. 2 of the patent application:



BEST AVAILABLE COPY

Since I_{sup} is related to the power-supply voltage V_{cc} , as the power-supply voltage V_{cc} changes, I_{sup} changes. However, the reference current I_{ref} , which is independent of V_{cc} , "tries" to stay the same. As a result, the voltage V_{sum} at node N changes, moving away from (increasing) a reference voltage (illustrated Gnd above) as the power-supply voltage V_{cc} increases, and moving toward the reference voltage Gnd as the power-supply voltage V_{cc} decreases.

The currents I_{sup} and I_{ref} have approximately equal temperature coefficients. As a result, the voltage V_{sum} at node N does not substantially change in response to temperature changes. Because both currents have the same or approximately the same temperature coefficient, the voltage V_{sum} is independent or approximately independent of temperature. This prevents changes in temperature from altering the value of V_{cc} at which the inverters 20 and 22 comparator circuit of FIG. 2 cause the switching circuit 8 (FIG. 1) to switch between the primary and secondary power sources 4 and 5, respectively.

Conversely, referring to Cordell's FIG. 1, unlike claim 59, which recites a maximum level of a reference current being independent of a supply voltage used to generate a supply-related current, both of Cordell's currents, I_3 and the current $(I_2 + I_3)$

through the resistor 40 depend on the voltage (which depends to the claim of supply voltage).

New claim 57 recites sinking only one current and sourcing only one current to a node. Conversely, referring to Cordell's FIG. 1, Cordell discloses sourcing two currents, I2 and I3, to the emitter of transistor 34, and sinking a third current, I2 + I3 from the emitter.

New claim 69 recites sinking from a comparison node a reference current having a first temperature coefficient, sourcing to the comparison node a current that is related to a power-supply voltage and that has approximately the first temperature coefficient; and comparing a voltage on the comparison node to a reference voltage.

Conversely, referring to Cordell's FIG. 1, Cordell does not compare a voltage on the emitter of the transistor 34 to a reference voltage.

BEST AVAILABLE COPY

CONCLUSION

In addition to the allowed claims 1-23, 28-34, 40-58, and 62-67, the amended claims 59 and 61, and the new claims 68 and 69 are in condition for allowance, making the application in condition for allowance subject to filing a supplemental reissue declaration. Such allowance is respectfully requested.

Please charge the \$204 for the two additional independent claims, and any additional fees, to Deposit Account No. 07-1897.

If the Examiner believes that a phone interview would be helpful, he is respectfully requested to contact the Applicants' attorney, Bryan Santarelli, at (425) 455-5575.

Respectfully submitted,

GRAYBEAL JACKSON HALEY LLP

Bryan A. Santarelli 47,695

Bryan A. Santarelli

Attorney for Applicants
Registration No. 37,580
155-108th Avenue N.E., Ste 350
Bellevue, WA 98004-5973
(425) 455-5575

Attachment: Marked-up version of amended and new claims

MARKED UP VERSION OF THE CLAIMS TO THE ORIGINAL CLAIMS DURING

59. A method, comprising:
sinking from a node generating a reference current having a first temperature coefficient; and
comparing the reference current to a supply-related current sourcing to the node a current having approximately the first temperature coefficient and being related to a power-supply voltage; that is related to a power-supply voltage and that has or has approximately the first temperature coefficient; and
comparing the reference current to the supply-related current.

61. The method of claim 59 wherein comparing the reference current comprises summing the reference current and the supply-related current at ~~a~~ the node to generate a voltage.

BEST AVAILABLE COPY

68. A method, comprising:
sinking from a node a reference current having a first temperature coefficient;
sourcing to the node a current that is related to a power-supply voltage and that has approximately the first temperature coefficient; and
neither sourcing nor sinking from the node a current other than the reference and supply-related currents.

69. A method comprising:
sinking from a comparison node a reference current having a first temperature coefficient;
sourcing to the comparison node a current that is related to a power-supply voltage and that has approximately the first temperature coefficient; and
comparing a voltage on the comparison node to a reference voltage.